(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



I AND LUNDON IN COUR BON CON COMENTA OF COME AND LUND HAVE COME COME AND THE COME COME COME

(43) International Publication Date 15 September 2005 (15.09.2005)

PCT

(10) International Publication Number WO 2005/084806 A1

 (51) International Patent Classification⁷: B01J 37/02, 35/04, B01D 46/24, 53/94, B05D 3/04, 7/22

(21) International Application Number:

PCT/GB2005/000870

(22) International Filing Date: 7 March 2005 (07.03.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0405015.9

5 March 2004 (05.03.2004) GB


- (71) Applicant (for all designated States except US): JOHN-SON MATTHEY PUBLIC LIMITED COMPANY [GB/GB]; 2-4 Cockspur Street, Trafalgar Square, London SW1Y 5BQ (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): TWIGG, Martyn,

Vincent [GB/GB]; 108 Ermine Street, Caxton, Cambridge CB3 8PQ (GB).

- (74) Agent: NUNN, Andrew, Dominic; Johnson Matthey Technology Centre, Blounts Court, Sonning Common, Reading RG4 9NII (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GII, GM, IIR, IIU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: METHOD OF MANUFACTURING A CATALYSED CERAMIC WALL-FLOW FILTER



(57) Abstract: A method of manufacturing a catalysed ceramic wall-flow filter comprising a plurality of channels comprises reducing the pressure in a pore structure of the channel walls relative to the surrounding atmospheric pressure, contacting a surface of the evacuated channel walls with a liquid containing at least one catalyst component or a precursor thereof, whereby the liquid permeates the evacuated channel walls, and drying and calcining the filter containing the catalyst component or its precursor. An apparatus (100) for use in the method comprises means (120) for sealingly isolating a plurality of channels of a ceramic wall-flow filter (14) from the surrounding atmosphere, means (160, 200, 220) for reducing the pressure in the isolated channels to below the surrounding atmospheric pressure thereby to establish a vacuum in the pore structure of the filter walls, at least one reservoir (260) for holding a liquid containing at least one catalyst component or a precursor thereof and means (310, 300, 220) for dosing the isolated and evacuated channels with a pre-determined quantity of the liquid.

ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- with international search report